



# PUBALI BANK LIMITED

## ICT OPERATION DIVISION

HEAD OFFICE, 26 DILKUSHA C/A, DHAKA.

PBL/HO/ICTOD/QUOTATION/700(3)/2022


February 24, 2022

### Notice inviting quotation for supply of Cisco Switch for our Bank.

Sealed quotations are hereby invited from bonafide Sellers, Manufacturers, Traders, Importers of CISCO Switch for supply of the same to our Bank as per following specifications.

#### Specifications of the Switch :

Access Switch POE (Quantity:01): C9200L-24P-4G		
Item Description	Technical Specifications	Bidder Specification
Quality	ISO 9001/9002 for manufacturer, FCC Class A/B for quality assurance	
Brand	To be mentioned by the bidder	
Model	To be mentioned by the bidder	
Environmental	Maintain International Quality Environmental Safety standard	
Form factor	Rack Mountable with Rack Mounting Kit	
Quantity	01 (One)	
Architecture	Should be highly performed fixed switch with wire rate Layer 2 and Layer 3 throughput on all the ports on the chassis. Should have minimum of 24 ports full PoE+ and 4x 1G fixed uplinks Switch should support stacking feature Switch should support Dual redundant platinum rate power supply and redundant Fans Switch should support SDN technology Should have min. 2GB DRAM & 4GB Flash	
Switching Performance	Minimum Switching capacity 56 Gbps full duplex or more Minimum Forwarding Throughput Minimum 41.66 Mpps or more	
Switch Layer 2 Services	Layer 2 switch ports and VLAN trunks IEEE 802.1Q VLAN encapsulation Support for up to 1000 VLANs ID Minimum 16,000 MAC Address Support minimum 9198 bytes Jumbo frame Support STP, RSTP, EtherChannel/LACP, VLAN Trunking Must have 5 MB of shared buffer for traffic/packet Queuing and processing	
Switch Layer 3 Services	Support Routing Protocols Static, RIP, Policy-Based Routing/Forwarding, Virtual redundant Routing Protocol (VRRP) from day 1 Support Routing protocols IS-IS, IP SLA, OSPFv3	



	<p>Minimum Up to 2,900 IPv4 route and 1,400 IPv6 route</p> <p>Support minimum 500 L3 VLAN Interfaces or Switched Virtual Interfaces</p> <p>Minimum 16,000 flow entries for security and traffic visibility.</p> <p>Support Internet Group Management Protocol (IGMP), PIM Stub etc.</p> <p>Support QoS with 802.1p Class of Service, Weighted Random Early Detection, DSCP field classification, Class-Based Weighted Fair Queuing, Shaped Round Robin scheduling or similar protocol</p>	
<b>Security features</b>	<p>Support 802.1X, Flexible Authentication, 802.1x Monitor Mode, and RADIUS Change of Authorization</p> <p>Support min.1400 ACL entries</p> <p>Support Port-based ACLs, VLAN ACLs</p> <p>Support Port Security, Dynamic ARP Inspection, and IP Source Guard</p> <p>Support OS, Firmware/BIOS &amp; patch authenticity as encrypted images to protect from unauthorized and modified/cracked images.</p> <p>Support OS validation during booting to protect from threats</p>	
<b>Management features</b>	<p>Support SNMP, syslog, NetFlow or SFlow, Data telemetry collection and correlation for performance monitoring.</p> <p>Support sampled NetFlow/SFlow, Switched Port Analyzer, Remote SPAN, shared NetFlow/SFlow policy, RSPAN and packet capture tool like Wireshark for troubleshooting and network visibility.</p> <p>Support Network automation with Open PnP, Containers, Python scripting, NETCONF, RESTCONF using YANG</p> <p>The switch must have at least 290,000 hours Mean Time Between Failure (MTBF) for hardware reliability.</p> <p>Should support centralize management platform for configuration rollout, change, backup, troubleshooting</p>	
<b>Manufacturer's part number</b>	Bidder should submit BOQ of proposed device including the details part numbers and Manufacturer's Warranty part number	
<b>Warranty</b>	Manufacturer's warranty part number should be mentioned, minimum 3 (Three) years warranty for OEM technical solution support, Patch & New Software Upgrade, RMA replacement should be provided for this unit from the date of commissioning.	

<b>Access Switch POE (Quantity:01): C9200L-48P-E</b>		
<b>Item Description</b>	<b>Technical Specifications</b>	<b>Bidder Specification</b>
<b>Quality</b>	ISO 9001/9002 for manufacturer, FCC Class A/B for quality assurance	
<b>Brand</b>	To be mentioned by the bidder	
<b>Model</b>	To be mentioned by the bidder	
<b>Environmental</b>	Maintain International Quality Environmental Safety standard	

<b>Form factor</b>	Rack Mountable with Rack Mounting Kit	
<b>Quantity</b>	01 (One)	
<b>Architecture</b>	Should be highly performed fixed switch with wire rate Layer 2 and Layer 3 throughput on all the ports on the chassis. Should have minimum of 24 ports full PoE+ and 4x 1G fixed uplinks Switch should support stacking feature Switch should support Dual redundant platinum rate power supply and redundant Fans Switch should support SDN technology Should have min. 2GB DRAM & 4GB Flash	
<b>Switching Performance</b>	Minimum Switching capacity 104 Gbps full duplex or more Minimum Forwarding Throughput Minimum 77.38 Mpps or more	
<b>Switch Layer 2 Services</b>	Layer 2 switch ports and VLAN trunks IEEE 802.1Q VLAN encapsulation Support for up to 1000 VLANs ID Minimum 16,000 MAC Address Support minimum 9198 bytes Jumbo frame Support STP, RSTP, EtherChannel/LACP, VLAN Trunking Must have 5 MB of shared buffer for traffic/packet Queuing and processing	
<b>Switch Layer 3 Services</b>	Support Routing Protocols Static, RIP, Policy-Based Routing/Forwarding, Virtual redundant Routing Protocol (VRRP) from day 1 Support Routing protocols IS-IS, IP SLA, OSPFv3 Minimum Up to 2,900 IPv4 route and 1,400 IPv6 route Support minimum 500 L3 VLAN Interfaces or Switched Virtual Interfaces Minimum 16,000 flow entries for security and traffic visibility. Support Internet Group Management Protocol (IGMP), PIM Stub etc. Support QoS with 802.1p Class of Service, Weighted Random Early Detection, DSCP field classification, Class-Based Weighted Fair Queuing, Shaped Round Robin scheduling or similar protocol	
<b>Security features</b>	Support 802.1X, Flexible Authentication, 802.1x Monitor Mode, and RADIUS Change of Authorization Support min.1400 ACL entries Support Port-based ACLs, VLAN ACLs Support Port Security, Dynamic ARP Inspection, and IP Source Guard Support OS, Firmware/BIOS & patch authenticity as encrypted images to protect from unauthorized and modified/cracked images. Support OS validation during booting to protect from threats	

Handwritten initials/signature.



<b>Management features</b>	<p>Support SNMP, syslog, NetFlow or SFlow, Data telemetry collection and correlation for performance monitoring.</p> <p>Support sampled NetFlow/SFlow, Switched Port Analyzer, Remote SPAN, shared NetFlow/SFlow policy, RSPAN and packet capture tool like Wireshark for troubleshooting and network visibility.</p> <p>Support Network automation with Open PnP, Containers, Python scripting, NETCONF, RESTCONF using YANG</p> <p>The switch must have at least 290,000 hours Mean Time Between Failure (MTBF) for hardware reliability.</p> <p>Should support centralize management platform for configuration rollout, change, backup, troubleshooting</p>	
<b>Manufacturer's part number</b>	Bidder should submit BOQ of proposed device including the details part numbers and Manufacturer's Warranty part number	
<b>Warranty</b>	Manufacturer's warranty part number should be mentioned, minimum 3 (Three) years warranty for OEM technical solution support, Patch & New Software Upgrade, RMA replacement should be provided for this unit from the date of commissioning.	

<b>Access Switch (Quantity:01): C9200L-24T-4G-E</b>		
<b>Item Description</b>	<b>Technical Specifications</b>	<b>Bidder Specification</b>
<b>Quality</b>	ISO 9001/9002 for manufacturer, FCC Class A/B for quality assurance	
<b>Brand</b>	To be mentioned by the bidder	
<b>Model</b>	To be mentioned by the bidder	
<b>Environmental</b>	Maintain International Quality Environmental Safety standard	
<b>Form factor</b>	Rack Mountable with Rack Mounting Kit	
<b>Quantity</b>	01 (One)	
<b>Architecture</b>	<p>Should be highly performed fixed switch with wire rate Layer 2 and Layer 3 throughput on all the ports on the chassis.</p> <p>Should have minimum of 24 x 1GE switch ports and 4 x 1G uplinks ports.</p> <p>Switch should support stacking feature</p> <p>Switch should support Dual redundant platinum rate power supply and redundant Fans</p> <p>Switch should support SDN technology</p> <p>Should have min. 2GB DRAM &amp; 4GB Flash</p>	
<b>Switching Performance</b>	<p>Minimum Switching capacity 56 Gbps full duplex or more</p> <p>Minimum Forwarding Throughput Minimum 41.66 Mpps or more</p>	
<b>Switch Layer 2 Services</b>	<p>Layer 2 switch ports and VLAN trunks</p> <p>IEEE 802.1Q VLAN encapsulation</p> <p>Support for up to 1000 VLANs ID</p> <p>Minimum 16,000 MAC Address</p> <p>Support minimum 9198 bytes Jumbo frame</p>	

	Support STP, RSTP, EtherChannel/LACP, VLAN Trunking Must have 5 MB of shared buffer for traffic/packet Queuing and processing	
<b>Switch Layer 3 Services</b>	Support Routing Protocols Static, RIP, Policy-Based Routing/Forwarding, Virtual redundant Routing Protocol (VRRP) from day 1 Support Routing protocols IS-IS, IP SLA, OSPFv3 Minimum Up to 2,900 IPv4 route and 1,400 IPv6 route Support minimum 500 L3 VLAN Interfaces or Switched Virtual Interfaces Minimum 16,000 flow entries for security and traffic visibility. Support Internet Group Management Protocol (IGMP), PIM Stub etc. Support QoS with 802.1p Class of Service, Weighted Random Early Detection, DSCP field classification, Class-Based Weighted Fair Queuing, Shaped Round Robin scheduling or similar protocol	
<b>Security features</b>	Support 802.1X, Flexible Authentication, 802.1x Monitor Mode, and RADIUS Change of Authorization Support min.1400 ACL entries Support Port-based ACLs, VLAN ACLs Support Port Security, Dynamic ARP Inspection, and IP Source Guard Support OS, Firmware/BIOS & patch authenticity as encrypted images to protect from unauthorized and modified/cracked images. Support OS validation during booting to protect from threats	
<b>Management features</b>	Support SNMP, syslog, NetFlow or SFlow, Data telemetry collection and correlation for performance monitoring. Support sampled NetFlow/SFlow, Switched Port Analyzer, Remote SPAN, shared NetFlow/SFlow policy, RSPAN and packet capture tool like Wireshark for troubleshooting and network visibility. Support Network automation with Open PnP, Containers, Python scripting, NETCONF, RESTCONF using YANG The switch must have at least 290,000 hours Mean Time Between Failure (MTBF) for hardware reliability. Should support centralize management platform for configuration rollout, change, backup, troubleshooting	
<b>Manufacturer's part number</b>	Bidder should submit BOQ of proposed device including the details part numbers and Manufacturer's Warranty part number	
<b>Warranty</b>	Manufacturer's warranty part number should be mentioned, minimum 3 (Three) years warranty for OEM technical solution support, Patch & New Software Upgrade, RMA replacement should be provided for this unit from the date of commissioning.	

<b>Access Switch (Quantity:01): C9200L-48T-4G-E</b>		
<b>Item Description</b>	<b>Technical Specifications</b>	<b>Bidder Specification</b>
<b>Quality</b>	ISO 9001/9002 for manufacturer, FCC Class A/B for quality assurance	
<b>Brand</b>	To be mentioned by the bidder	
<b>Model</b>	To be mentioned by the bidder	
<b>Environmental</b>	Maintain International Quality Environmental Safety standard	
<b>Form factor</b>	Rack Mountable with Rack Mounting Kit	
<b>Quantity</b>	01 (One)	
<b>Architecture</b>	Should be highly performed fixed switch with wire rate Layer 2 and Layer 3 throughput on all the ports on the chassis. Should have minimum of 48 x 1GE switch ports and 4 x 1G uplinks ports. Switch should support stacking feature Switch should support Dual redundant platinum rate power supply and redundant Fans Switch should support SDN technology Should have min. 2GB DRAM & 4GB Flash	
<b>Switching Performance</b>	Minimum Switching capacity 104 Gbps full duplex or more Minimum Forwarding Throughput Minimum 77.38 Mpps or more	
<b>Switch Layer 2 Services</b>	Layer 2 switch ports and VLAN trunks IEEE 802.1Q VLAN encapsulation Support for up to 1000 VLANs ID Minimum 16,000 MAC Address Support minimum 9198 bytes Jumbo frame Support STP, RSTP, EtherChannel/LACP, VLAN Trunking Must have 5 MB of shared buffer for traffic/packet Queuing and processing	
<b>Switch Layer 3 Services</b>	Support Routing Protocols Static, RIP, Policy-Based Routing/Forwarding, Virtual redundant Routing Protocol (VRRP) from day 1 Support Routing protocols IS-IS, IP SLA, OSPFv3 Minimum Up to 2,900 IPv4 route and 1,400 IPv6 route Support minimum 500 L3 VLAN Interfaces or Switched Virtual Interfaces Minimum 16,000 flow entries for security and traffic visibility. Support Internet Group Management Protocol (IGMP), PIM Stub etc. Support QoS with 802.1p Class of Service, Weighted Random Early Detection, DSCP field classification, Class-Based Weighted Fair Queuing, Shaped Round Robin scheduling or similar protocol	
<b>Security features</b>	Support 802.1X, Flexible Authentication, 802.1x Monitor Mode, and RADIUS Change of Authorization	

	<p>Support min.1400 ACL entries</p> <p>Support Port-based ACLs, VLAN ACLs</p> <p>Support Port Security, Dynamic ARP Inspection, and IP Source Guard</p> <p>Support OS, Firmware/BIOS &amp; patch authenticity as encrypted images to protect from unauthorized and modified/cracked images.</p> <p>Support OS validation during booting to protect from threats</p>	
<b>Management features</b>	<p>Support SNMP, syslog, NetFlow or SFlow, Data telemetry collection and correlation for performance monitoring.</p> <p>Support sampled NetFlow/SFlow, Switched Port Analyzer, Remote SPAN, shared NetFlow/SFlow policy, RSPAN and packet capture tool like Wireshark for troubleshooting and network visibility.</p> <p>Support Network automation with Open PnP, Containers, Python scripting, NETCONF, RESTCONF using YANG</p> <p>The switch must have at least 290,000 hours Mean Time Between Failure (MTBF) for hardware reliability.</p> <p>Should support centralize management platform for configuration rollout, change, backup, troubleshooting and performance analysis feature.</p>	
<b>Manufacturer's part number</b>	Bidder should submit BOQ of proposed device including the details part numbers and Manufacturer's Warranty part number	
<b>Warranty</b>	Manufacturer's warranty part number should be mentioned, minimum 3 (Three) years warranty for OEM technical solution support, Patch & New Software Upgrade, RMA replacement should be provided for this unit from the date of commissioning.	

**Terms and conditions:-**

- 1) The offer must be submitted through "**Offering Sheet**" enclosed with the schedule.
- 2) The Switch will be under comprehensive Warranty for **full 3(three) years** from the date of delivery.
- 3) In case of any trouble with the Switch within the warranty period the supplier shall have to replace/repair the Item free of cost at the premises of the Branch/Office where it will be supplied within 24(twenty four) hours. If the Item is not in repairable condition on the premises, it should be replaced by a similar one within 24 (twenty four) hours from getting the information of trouble prior to bring the same at their end for repairing purpose. In case of failure of the supplier, the Bank shall have the right to get the replacement or repairing works done by other agency at the cost of the supplier. Such costs will be recovered from the supplier and the supplier shall have no objection to it.
- 4) Payment of the bills will be made from ICT Operation Division, Head Office, after delivery of the same to the Branches/Offices as per terms of the Supply Order.
- 5) **10% (ten percent) of the bill amount** will be retained as Security Money which will be paid to the supplier after expiry of the warranty period at the satisfaction of the purchaser.

- 6) All Tax, Vat, Govt. Duties etc. will be deducted from the bill as per rule prior payment of the same.
- 8) **Successful bidder must ensure delivery of Switches within 15(fifteen) days of getting work order.**
- 9) The authority reserves the right either to accept or to reject all or any offer without assigning any reason.
- 10) Bank is not bound to accept the lowest Quotation. To be successful in the bid, quality of the offered items, financial capability, reputation etc. of the firm as assessed by the Bank are the prime factors for consideration.
- 10) The successful bidder shall have to inform the Bank 1(one) month before if they want to discontinue supply of the CISCO Switch.
- 11) Photocopy of Trade License, TIN Certificate, VAT registration Certificate (if any), Financial Solvency Certificate (if any), Appreciation letter, Major client List and Company profile to be submitted with the Quotation.

Offer / Bid to be dropped in the Tender Box kept in **Establishment Division, Pubali Bank Limited, Head Office, 12<sup>th</sup> Floor, 26 Dilkusha C/A, Dhaka** by 11-00 a.m. up to 09-03-2022 which will be opened on the same day at 11.30 a.m. in presence of the bidders present (if any).

Sd/-

(Md. Aminul Islam)  
Asst. General Manager


Sd/-

(Md. Helal Uddin)  
GM & Division Head

CC TO : The Member Secretary, Purchase Committee, Pubali Bank Ltd., Head Office, Dhaka for information and necessary action.

CC TO : Notice Board, Pubali Bank Ltd., Head Office, Dhaka .

CC TO : [www.pubalibangla.com](http://www.pubalibangla.com)

  
Asst. General Manager

  
GM & Division Head



# OFFERING SHEET

(To be submitted alongwith the offer)

**Tenderer's Name :**

**Address :**

<b>Access Switch POE (Quantity:01): C9200L-24P-4G</b>			
<b>Item Description</b>	<b>Technical Specifications</b>	<b>Bidder Specification</b>	<b>Price (including VAT &amp; Tax)</b>
<b>Quality</b>	ISO 9001/9002 for manufacturer, FCC Class A/B for quality assurance		
<b>Brand</b>	To be mentioned by the bidder		
<b>Model</b>	To be mentioned by the bidder		
<b>Environmental</b>	Maintain International Quality Environmental Safety standard		
<b>Form factor</b>	Rack Mountable with Rack Mounting Kit		
<b>Quantity</b>	01 (One)		
<b>Architecture</b>	Should be highly performed fixed switch with wire rate Layer 2 and Layer 3 throughput on all the ports on the chassis. Should have minimum of 24 ports full PoE+ and 4x 1G fixed uplinks Switch should support stacking feature Switch should support Dual redundant platinum rate power supply and redundant Fans Switch should support SDN technology Should have min. 2GB DRAM & 4GB Flash		
<b>Switching Performance</b>	Minimum Switching capacity 56 Gbps full duplex or more Minimum Forwarding Throughput Minimum 41.66 Mpps or more		
<b>Switch Layer 2 Services</b>	Layer 2 switch ports and VLAN trunks IEEE 802.1Q VLAN encapsulation Support for up to 1000 VLANs ID Minimum 16,000 MAC Address Support minimum 9198 bytes Jumbo frame Support STP, RSTP, EtherChannel/LACP, VLAN Trunking Must have 5 MB of shared buffer for traffic/packet Queuing and processing		
<b>Switch Layer 3 Services</b>	Support Routing Protocols Static, RIP, Policy-Based Routing/Forwarding, Virtual redundant Routing Protocol (VRRP) from day 1 Support Routing protocols IS-IS, IP SLA, OSPFv3 Minimum Up to 2,900 IPv4 route and 1,400 IPv6 route Support minimum 500 L3 VLAN Interfaces or Switched Virtual Interfaces		

	<p>Minimum 16,000 flow entries for security and traffic visibility.</p> <p>Support Internet Group Management Protocol (IGMP), PIM Stub etc.</p> <p>Support QoS with 802.1p Class of Service, Weighted Random Early Detection, DSCP field classification, Class-Based Weighted Fair Queuing, Shaped Round Robin scheduling or similar protocol</p>		
<b>Security features</b>	<p>Support 802.1X, Flexible Authentication, 802.1x Monitor Mode, and RADIUS Change of Authorization</p> <p>Support min.1400 ACL entries</p> <p>Support Port-based ACLs, VLAN ACLs</p> <p>Support Port Security, Dynamic ARP Inspection, and IP Source Guard</p> <p>Support OS, Firmware/BIOS &amp; patch authenticity as encrypted images to protect from unauthorized and modified/cracked images.</p> <p>Support OS validation during booting to protect from threats</p>		
<b>Management features</b>	<p>Support SNMP, syslog, NetFlow or SFlow, Data telemetry collection and correlation for performance monitoring.</p> <p>Support sampled NetFlow/SFlow, Switched Port Analyzer, Remote SPAN, shared NetFlow/SFlow policy, RSPAN and packet capture tool like Wireshark for troubleshooting and network visibility.</p> <p>Support Network automation with Open PnP, Containers, Python scripting, NETCONF, RESTCONF using YANG</p> <p>The switch must have at least 290,000 hours Mean Time Between Failure (MTBF) for hardware reliability.</p> <p>Should support centralize management platform for configuration rollout, change, backup, troubleshooting</p>		
<b>Manufacturer's part number</b>	Bidder should submit BOQ of proposed device including the details part numbers and Manufacturer's Warranty part number		
<b>Warranty</b>	Manufacturer's warranty part number should be mentioned, minimum 3 (Three) years warranty for OEM technical solution support, Patch & New Software Upgrade, RMA replacement should be provided for this unit from the date of commissioning.		

<b>Access Switch POE (Quantity:01): C9200L-48P-E</b>			
<b>Item Description</b>	<b>Technical Specifications</b>	<b>Bidder Specification</b>	<b>Price (including VAT &amp; Tax)</b>
<b>Quality</b>	ISO 9001/9002 for manufacturer, FCC Class A/B for quality assurance		
<b>Brand</b>	To be mentioned by the bidder		
<b>Model</b>	To be mentioned by the bidder		
<b>Environmental</b>	Maintain International Quality Environmental Safety standard		

<b>Form factor</b>	Rack Mountable with Rack Mounting Kit		
<b>Quantity</b>	01 (One)		
<b>Architecture</b>	<p>Should be highly performed fixed switch with wire rate Layer 2 and Layer 3 throughput on all the ports on the chassis.</p> <p>Should have minimum of 24 ports full PoE+ and 4x 1G fixed uplinks</p> <p>Switch should support stacking feature</p> <p>Switch should support Dual redundant platinum rate power supply and redundant Fans</p> <p>Switch should support SDN technology</p> <p>Should have min. 2GB DRAM &amp; 4GB Flash</p>		
<b>Switching Performance</b>	<p>Minimum Switching capacity 104 Gbps full duplex or more</p> <p>Minimum Forwarding Throughput Minimum 77.38 Mpps or more</p>		
<b>Switch Layer 2 Services</b>	<p>Layer 2 switch ports and VLAN trunks</p> <p>IEEE 802.1Q VLAN encapsulation</p> <p>Support for up to 1000 VLANs ID</p> <p>Minimum 16,000 MAC Address</p> <p>Support minimum 9198 bytes Jumbo frame</p> <p>Support STP, RSTP, EtherChannel/LACP, VLAN Trunking</p> <p>Must have 5 MB of shared buffer for traffic/packet Queuing and processing</p>		
<b>Switch Layer 3 Services</b>	<p>Support Routing Protocols Static, RIP, Policy-Based Routing/Forwarding, Virtual redundant Routing Protocol (VRRP) from day 1</p> <p>Support Routing protocols IS-IS, IP SLA, OSPFv3</p> <p>Minimum Up to 2,900 IPv4 route and 1,400 IPv6 route</p> <p>Support minimum 500 L3 VLAN Interfaces or Switched Virtual Interfaces</p> <p>Minimum 16,000 flow entries for security and traffic visibility.</p> <p>Support Internet Group Management Protocol (IGMP), PIM Stub etc.</p> <p>Support QoS with 802.1p Class of Service, Weighted Random Early Detection, DSCP field classification, Class-Based Weighted Fair Queuing, Shaped Round Robin scheduling or similar protocol</p>		
<b>Security features</b>	<p>Support 802.1X, Flexible Authentication, 802.1x Monitor Mode, and RADIUS Change of Authorization</p> <p>Support min.1400 ACL entries</p> <p>Support Port-based ACLs, VLAN ACLs</p> <p>Support Port Security, Dynamic ARP Inspection, and IP Source Guard</p> <p>Support OS, Firmware/BIOS &amp; patch authenticity as encrypted images to protect from unauthorized and modified/cracked images.</p> <p>Support OS validation during booting to protect from</p>		

	threats		
<b>Management features</b>	<p>Support SNMP, syslog, NetFlow or SFlow, Data telemetry collection and correlation for performance monitoring.</p> <p>Support sampled NetFlow/SFlow, Switched Port Analyzer, Remote SPAN, shared NetFlow/SFlow policy, RSPAN and packet capture tool like Wireshark for troubleshooting and network visibility.</p> <p>Support Network automation with Open PnP, Containers, Python scripting, NETCONF, RESTCONF using YANG</p> <p>The switch must have at least 290,000 hours Mean Time Between Failure (MTBF) for hardware reliability.</p> <p>Should support centralize management platform for configuration rollout, change, backup, troubleshooting</p>		
<b>Manufacturer's part number</b>	Bidder should submit BOQ of proposed device including the details part numbers and Manufacturer's Warranty part number		
<b>Warranty</b>	Manufacturer's warranty part number should be mentioned, minimum 3 (Three) years warranty for OEM technical solution support, Patch & New Software Upgrade, RMA replacement should be provided for this unit from the date of commissioning.		

<b>Access Switch (Quantity:01): C9200L-24T-4G-E</b>			
<b>Item Description</b>	<b>Technical Specifications</b>	<b>Bidder Specification</b>	<b>Price (including VAT &amp; Tax)</b>
<b>Quality</b>	ISO 9001/9002 for manufacturer, FCC Class A/B for quality assurance		
<b>Brand</b>	To be mentioned by the bidder		
<b>Model</b>	To be mentioned by the bidder		
<b>Environmental</b>	Maintain International Quality Environmental Safety standard		
<b>Form factor</b>	Rack Mountable with Rack Mounting Kit		
<b>Quantity</b>	01 (One)		
<b>Architecture</b>	<p>Should be highly performed fixed switch with wire rate Layer 2 and Layer 3 throughput on all the ports on the chassis.</p> <p>Should have minimum of 24 x 1GE switch ports and 4 x 1G uplinks ports.</p> <p>Switch should support stacking feature</p> <p>Switch should support Dual redundant platinum rate power supply and redundant Fans</p> <p>Switch should support SDN technology</p> <p>Should have min. 2GB DRAM &amp; 4GB Flash</p>		
<b>Switching Performance</b>	<p>Minimum Switching capacity 56 Gbps full duplex or more</p> <p>Minimum Forwarding Throughput Minimum 41.66 Mpps or more</p>		
<b>Switch Layer 2 Services</b>	<p>Layer 2 switch ports and VLAN trunks</p> <p>IEEE 802.1Q VLAN encapsulation</p> <p>Support for up to 1000 VLANs ID</p>		

	<p>Minimum 16,000 MAC Address</p> <p>Support minimum 9198 bytes Jumbo frame</p> <p>Support STP, RSTP, EtherChannel/LACP, VLAN Trunking</p> <p>Must have 5 MB of shared buffer for traffic/packet Queuing and processing</p>		
<b>Switch Layer 3 Services</b>	<p>Support Routing Protocols Static, RIP, Policy-Based Routing/Forwarding, Virtual redundant Routing Protocol (VRRP) from day 1</p> <p>Support Routing protocols IS-IS, IP SLA, OSPFv3</p> <p>Minimum Up to 2,900 IPv4 route and 1,400 IPv6 route</p> <p>Support minimum 500 L3 VLAN Interfaces or Switched Virtual Interfaces</p> <p>Minimum 16,000 flow entries for security and traffic visibility.</p> <p>Support Internet Group Management Protocol (IGMP), PIM Stub etc.</p> <p>Support QoS with 802.1p Class of Service, Weighted Random Early Detection, DSCP field classification, Class-Based Weighted Fair Queuing, Shaped Round Robin scheduling or similar protocol</p>		
<b>Security features</b>	<p>Support 802.1X, Flexible Authentication, 802.1x Monitor Mode, and RADIUS Change of Authorization</p> <p>Support min.1400 ACL entries</p> <p>Support Port-based ACLs, VLAN ACLs</p> <p>Support Port Security, Dynamic ARP Inspection, and IP Source Guard</p> <p>Support OS, Firmware/BIOS &amp; patch authenticity as encrypted images to protect from unauthorized and modified/cracked images.</p> <p>Support OS validation during booting to protect from threats</p>		
<b>Management features</b>	<p>Support SNMP, syslog, NetFlow or SFlow, Data telemetry collection and correlation for performance monitoring.</p> <p>Support sampled NetFlow/SFlow, Switched Port Analyzer, Remote SPAN, shared NetFlow/SFlow policy, RSPAN and packet capture tool like Wireshark for troubleshooting and network visibility.</p> <p>Support Network automation with Open PnP, Containers, Python scripting, NETCONF, RESTCONF using YANG</p> <p>The switch must have at least 290,000 hours Mean Time Between Failure (MTBF) for hardware reliability.</p> <p>Should support centralize management platform for configuration rollout, change, backup, troubleshooting</p>		
<b>Manufacturer's part number</b>	Bidder should submit BOQ of proposed device including the details part numbers and Manufacturer's Warranty part number		
<b>Warranty</b>	Manufacturer's warranty part number should be mentioned, minimum 3 (Three) years warranty for OEM technical solution support, Patch & New Software Upgrade, RMA replacement should be provided for this unit from the date		

	of commissioning.		
--	-------------------	--	--

<b>Access Switch (Quantity:01): C9200L-48T-4G-E</b>			
<b>Item Description</b>	<b>Technical Specifications</b>	<b>Bidder Specification</b>	<b>Price (including VAT &amp; Tax)</b>
<b>Quality</b>	ISO 9001/9002 for manufacturer, FCC Class A/B for quality assurance		
<b>Brand</b>	To be mentioned by the bidder		
<b>Model</b>	To be mentioned by the bidder		
<b>Environmental</b>	Maintain International Quality Environmental Safety standard		
<b>Form factor</b>	Rack Mountable with Rack Mounting Kit		
<b>Quantity</b>	01 (One)		
<b>Architecture</b>	Should be highly performed fixed switch with wire rate Layer 2 and Layer 3 throughput on all the ports on the chassis. Should have minimum of 48 x 1GE switch ports and 4 x 1G uplinks ports. Switch should support stacking feature Switch should support Dual redundant platinum rate power supply and redundant Fans Switch should support SDN technology Should have min. 2GB DRAM & 4GB Flash		
<b>Switching Performance</b>	Minimum Switching capacity 104 Gbps full duplex or more Minimum Forwarding Throughput Minimum 77.38 Mpps or more		
<b>Switch Layer 2 Services</b>	Layer 2 switch ports and VLAN trunks IEEE 802.1Q VLAN encapsulation Support for up to 1000 VLANs ID Minimum 16,000 MAC Address Support minimum 9198 bytes Jumbo frame Support STP, RSTP, EtherChannel/LACP, VLAN Trunking Must have 5 MB of shared buffer for traffic/packet Queuing and processing		
<b>Switch Layer 3 Services</b>	Support Routing Protocols Static, RIP, Policy-Based Routing/Forwarding, Virtual redundant Routing Protocol (VRRP) from day 1 Support Routing protocols IS-IS, IP SLA, OSPFv3 Minimum Up to 2,900 IPv4 route and 1,400 IPv6 route Support minimum 500 L3 VLAN Interfaces or Switched Virtual Interfaces Minimum 16,000 flow entries for security and traffic visibility. Support Internet Group Management Protocol (IGMP), PIM Stub etc. Support QoS with 802.1p Class of Service, Weighted Random Early Detection, DSCP field classification, Class-Based Weighted Fair Queuing, Shaped Round Robin		

	scheduling or similar protocol		
<b>Security features</b>	<p>Support 802.1X, Flexible Authentication, 802.1x Monitor Mode, and RADIUS Change of Authorization</p> <p>Support min.1400 ACL entries</p> <p>Support Port-based ACLs, VLAN ACLs</p> <p>Support Port Security, Dynamic ARP Inspection, and IP Source Guard</p> <p>Support OS, Firmware/BIOS &amp; patch authenticity as encrypted images to protect from unauthorized and modified/cracked images.</p> <p>Support OS validation during booting to protect from threats</p>		
<b>Management features</b>	<p>Support SNMP, syslog, NetFlow or SFlow, Data telemetry collection and correlation for performance monitoring.</p> <p>Support sampled NetFlow/SFlow, Switched Port Analyzer, Remote SPAN, shared NetFlow/SFlow policy, RSPAN and packet capture tool like Wireshark for troubleshooting and network visibility.</p> <p>Support Network automation with Open PnP, Containers, Python scripting, NETCONF, RESTCONF using YANG</p> <p>The switch must have at least 290,000 hours Mean Time Between Failure (MTBF) for hardware reliability.</p> <p>Should support centralize management platform for configuration rollout, change, backup, troubleshooting and performance analysis feature.</p>		
<b>Manufacturer's part number</b>	Bidder should submit BOQ of proposed device including the details part numbers and Manufacturer's Warranty part number		
<b>Warranty</b>	Manufacturer's warranty part number should be mentioned, minimum 3 (Three) years warranty for OEM technical solution support, Patch & New Software Upgrade, RMA replacement should be provided for this unit from the date of commissioning.		

**Authorised Signature**